TELSTAR ELECTRONICS CORP.

9025 ETON AVE. STE.A, GANOGA PARK, CA 91304
TEL 818-882-2018 FAX 818-882-5137

Email Address: sales@telstarcorp.com
Web Address : www.telstarcorp.com

ATEC-SP2180-30W Sub-woofer with 2.1 Channel Class D Amplifier

1. 4" Speaker, DC24V INPUT
2. RATED POWER : 30W 4 Ohm 24V
   Max. Rated Power : 35W 4 Ohm 24V
3. Stereo Full range Satellite Speaker Outputs
4. 0-20kHz System rated Frequency Range
5. 100dB SPL Max Woofer Output
6. Rated Sensitivity : 80 dB +/- 3 dB
7. Dimension : 177x127x127mm (WxHxD)
8. 4" Vibrating Membrane & Frame
9. Black MDF Construction

* Amplifier Key Features

* 118Hz 18/dB Octave Crossover
* Woofer Level Control
* Master Volume Controls
* Color Coded RCA Connections for Full Range Speaker Hook Up
* 3.5mm Stereo "Mini-Jack" Audio Input
* 2.1mm DC Power Input
* Red LED Power Light

Amplifier Output Specifications :

Left or Righter Full range : 15W 8 Ohm 1%

Subwoofer : 38W RMS, 4 Ohm, Max 50W, THD1%

Amplifier IC: FT3129 ClassD

SNR : >96dB

DC Input : 24V/4A